

TL系列 I/O扩展模块



EtherCAT标准从站模块，适配标准 EtherCAT主站设备



功能丰富，可满足不同应用场合需求



模块/通道状态灯，易于诊断



免工具接线，快人一步



种类丰富，满足多样需求



产品选型

Product selection

产品型号 Product model	描述 Description
TL0100	EtherCAT耦合器 EtherCAT coupler
TL9000	终端盖板模块 Terminal cover module
TL1016	16 通道数字量输入, PNP/24V有效/漏型 16-channel DI, PNP/24V active/sink
TL1116	16 通道数字量输入, NPN/0V有效/源型 16-channel DI, NPN/0V active/source
TL2016	16 通道数字量输出, 0.5A/PNP/24V有效/源型 16-channel DO, 0.5A/PNP/24V active/source
TL2116	16 通道数字量输出, 0.5A/NPN/0V有效/漏型 16-channel DO, 0.5A/NPN/0V active/sink
TL1516	8通道数字量输入, PNP/24V有效/漏型, NPN/0V有效/源型 8-channel DI, PNP/24V active/sink, NPN/0V active/source 8通道数字量输出, 0.5A/PNP/24V/源型 8-channel DO, 0.5A/PNP/24V/source
TL3104	4通道模拟量-电压输入, 0-5VDC/0-10VDC/±5VDC/±10VDC, 16位, 通道隔离 4-channel analogue voltage input, 0-5VDC/0-10VDC/±5VDC/±10VDC, 16-bit, channel isolated
TL3108	8通道模拟量-电压输入, 0-5VDC/0-10VDC/±5VDC/±10VDC, 16位 8-channel analogue voltage input, 0-5VDC/0-10VDC/±5VDC/±10VDC, 16-bit
TL3204	4通道模拟量-电流输入, 0&4-20mA, 16位 4-channel analogue current input, 0&4-20mA, 16-bit
TL3208	8通道模拟量-电流输入, 0&4-20mA, 16位 8-channel analogue current input, 0&4-20mA, 16-bit
TL4104	4通道电压输出, 0-5VDC/0-10VDC/±5VDC/±10VDC, 16位 4-channel voltage output, 0-5VDC/0-10VDC/±5VDC/±10VDC, 16-bit
TL4204	4通道模拟量电流输出, 0&4-20mA/16位 4-channel analogue current output, 0&4-20mA/16-bit
TL3703	3通道热电阻输入, RTD-PT100 通道非隔离 3-channel thermal resistance input, RTD-PT100, channel non-isolated
TL3704	4通道热电阻输入, RTD-PT100 通道隔离 4-channel thermal resistance input, RTD-PT100, channel isolated
TL3803	3通道热电阻输入, RTD-PT1000 3-channel thermal resistance input, RTD-PT1000
TL3904	4通道热电偶输入, TC-J/K/E/T/S/R/B/N/C型 4-channel thermocouple input, TC-J/K/E/T/S/R/B/N/C
TL5102	2通道编码器输入, 5V单端, 输入频率≤1.5MHz 2-channel encoder input, 5V single-ended, input frequency ≤ 1.5MHz
TL5202	2通道编码器输入, 24V单端, 输入频率≤500KHz 2-channel encoder input, 24V single-ended, input frequency ≤ 500KHz
TL6001	1通道串口模块, Modbus主站/Modbus从站/自由协议 1-channel serial port module, Modbus master/Modbus slave/free protocol
TL9410	电源扩展模块, SV: 5V/2A FV: 24V/8A Power expansion module, SV: 5V/2A FV: 24V/8A